

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

Fig. 1




Fig. 2





Fig. 3



color offset value

色	オフセット値
K	a 1
C	a 2
M	a 3
Y	a 4

Fig. 4

color offset value

色	オフセット値
K	b 1
C	b 2
M	b 3
Y	b 4

Fig. 5

offset value

color	main controller	engine controller
オフセット値		
	メインコントローラ	エンジンコントローラ
K	c1	d1
C	c2	d2
M	c3	d3
Y	c4	d4

Fig. 6




Fig. 7

Fig. 8





Fig. 9



Hidenori KIN
 DEVICE AND METHOD OF CALCULATING
 Darryl Mexic
 202-293-7060
 March 26, 2004
 7 of 9

3: charger

6: exposer

12: display

49Y, 49C, 49M, 49K: connector

60: temperature sensor

77: vertical synchronization sensor

102: exposure controller


103: charging controller

104: development controller

108: connector


113: image memory

Fig. 10



- 102: exposure controller
- 201: comparator
- 202: discriminator
- 203, 204, 205: counter
- 206: calculator
- 207: coefficient table
- 210: counter

Fig. 11



102: exposure controller

201: comparator

202: discriminator

203, 204, 205: counter

206: calculator

207: coefficient table

Q8071
Hidenori KIN
DEVICE AND METHOD OF CALCULATING
Darryl Mexic
March 26, 2004
2025293-7060
9 of 9